# SAFETY DATA SHEET

# **SECTION 1 - PRODUCT & COMPANY IDENTIFICATION**

Product Name: 399 Phenolic Epoxy Tank Lining Product Code: 399-Activator LT35 Black

Trade Name: 399-Activator LT35 Black

Adams Paint Mfg Company 1416 N University Ave Lubbock, Tx 79415

Telephone Number: 806-763-2944 Web Site: adamspaintmfg.com

Product Use: See Product Data Sheet

Not recommended for: See Product Data Sheet

**Emergency Contacts & Phone Numbers** 

Chemtrec: 800-424-9300

SDS Request Line: 806-763-2944

# **SECTION 2 - HAZARDS IDENTIFICATION**

# **GHS Ratings:**

	Flammable liquid	4	Flash point >= 60°C (140°F) and <= 93°C (200°F)
	Oral Toxicity	Acute Tox. 4	Oral>300+<=2000mg/kg
	Dermal Toxicity	Acute Tox. 4	Dermal>1000+<=2000mg/kg
	Skin corrosive	1A	Destruction of dermal tissue: Exposure < 3 min. Observation < 1 hour, visible necrosis in at least one animal
	Eye corrosive	1	Serious eye damage: Irreversible damage 21 days after exposure, Draize score: Corneal opacity >= 3, Iritis > 1.5
	Skin sensitizer	1	Skin sensitizer
	Mutagen	1B	Known to produce heritable mutations in human germ cellsSubcategory 1B, Positive results: In vivo heritable germ cell tests in mammals, Human germ cell tests, In vivo somatic mutagenicity tests, combined with some evidence of germ cell mutagenicity
	Carcinogen	2	Limited evidence of human or animal carcinogenicity
	Reproductive toxin	1B	Presumed, Based on experimental animals
GHS H	azards		
	H227 H302 H312	Combustible liquid Harmful if swallowed Harmful in contact wi	

H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H340	May cause genetic defects
H351	Suspected of causing cancer
H360	May damage fertility or the unborn child

# **GHS Precautions**

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat, sparks, open flames, hot surfaces and other ignition
	sources - No smoking
P235	Keep cool
P260	Do not breathe dust, fumes, gas, mist, vapors or spray
P261	Avoid breathing dust, fumes, gas, mist, vapors or spray

P264 Wash thoroughly after handling

SDS for: 399-Activator LT35 Black Page 1 of 6

P270 Do not eat, drink or smoke when using this product P272 Contaminated work clothing should not be allowed out of the workplace P280 Wear protective gloves, protective clothing, eye protection and face protection P281 Use personal protective equipment as required P310 Immediately call a POISON CENTER or physician P312 Call a POISON CENTER or physician if you feel unwell P321 Specific treatment (see Section 4 of SDS on this label) P322 Specific measures (see Section 4 of SDS on this label) P330 Rinse mouth P363 Wash contaminated clothing before reuse P301+P312 IF SWALLOWED: Call a POISON CENTER or physician if you feel unwell P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting P302+P352 IF ON SKIN: Wash with soap and water P303+P361+P353 IF ON SKIN: Take off immediately all contaminated clothing. Rinse skin with water P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing P305+P351+P338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing P308+P313 IF exposed or concerned: Get medical attention P333+P313 If skin irritation or a rash occurs: Get medical attention P370+P378 In case of fire: Use dry chemical, foam, carbon dioxide or water fog for extinction P405 Store locked up P403+P235 Store in a well ventilated place. Keep cool P501 Dispose of contents and container in accordance with local and national regulations

# Signal Word: Danger



#### SECTION 3 - COMPOSITION INFORMATION ON INGREDIENTS

Chemical Name	CAS number	Weight Concentration %
Formaldehyde, oligomeric reaction products with phenol and m-phenylenebis(methylamine)	57214-10-5	40.00% - 50.00%
Phenol	108-95-2	20.00% - 30.00%
1,3-Benzenedimethanamine	1477-55-0	20.00% - 30.00%
Carbon black	1333-86-4	0.10% - 1.00%

## **SECTION 4 - FIRST AID MEASURES**

<u>Inhalation</u>: Move to fresh air. If not breathing, give artifitial respiration or give oxygen by trained personnel. In case of unconsciousness place patient stably on side position for transportation. Seek immediate medical attention.

**Eye Contact**: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting upper and lower eyelids. Check for and remove any contact lenses. Get medical attention.

**Skin Contact:** Flush contaminated skin with plenty soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. In the event of any complaints or symptoms, avoid further exposure. Get medical attention.

Ingestion: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give

SDS for: 399-Activator LT35 Black Page 2 of 6

small quantities of water to drink. DO NOT induce vomiting. If vomiting occurs, the head should be kept low so that the vomit does not enter the lungs. Get medical attention immediately. Never give anything by mouth to an unconscious person.

**Notes to Physician:** No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

# **SECTION 5 - FIRE FIGHTING MEASURES**

Flash Point: 79 C (174 F)

LEL: 2.00 UEL:

Suitable Extinguishing Media: Use dry chemical, foam, carbon dioxide, or water fog to extinguish fire.

<u>Specific Hazards arising from the Chemical</u>: Minimize breathing gases, vapors, fumes or decomposition products.

Hazardous Combustion Products: No further relevant information available.

<u>Protection of Firefighters</u>: Water may be unsuitable as an extinguishing media, but helpful in keeping adjacent containers cool. Move containers from fire area if this can be done without risk. If a leak or spill has ignited, use water spray to disperse the vapors and to protect the men attempting to stop leak.

<u>Protective Equipment and Precautions for Firefighters</u>: Wear self-contained breathing apparatus and full protective gear.

# **SECTION 6 - ACCIDENTAL RELEASE MEASURES**

<u>Personal Precautions</u>: Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Avoid breathing vapor or mist. Provide adequate ventilation. Use proper personal protective equipment as listed in Section 8.

<u>Environmental Precautions</u>: Avoid runoff into storm sewers, ditches and waterways. Inform the relevant authorities if the product has caused environmental pollution.

<u>Methods for Containment and Clean Up</u>: Absorb spill with liquid-binding material (sand, diatomite, acid binders, universal binders or other inert material) then place in a container for chemical waste.

# **SECTION 7 - HANDLING AND STORAGE**

<u>Handling</u>: Use with adequate ventilation. Avoid breathing vapor and contacts with eyes, skin and clothing. Do not reuse containers without proper cleaning or reconditioning.

<u>Hygiene Practices</u>: Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling vapor or mist. <u>Storage</u>: Store in a cool dry, well ventilated area away from incompatible substances. Keep container tightly closed when not in use. Use appropriate containment to avoid environmental contamination.

#### SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Formaldehyde, oligomeric reaction products with phenol and m-phenylenebis (methylamine) 57214-10-5	Not Established	Not Established	Not Established
Phenol 108-95-2	5 ppm TWA; 19 mg/m3 TWA	5 ppm TWA	NIOSH: 5 ppm TWA; 19 mg/m3 TWA 15.6 ppm Ceiling (15 min); 60 mg/m3 Ceiling (15 min)
1,3-Benzenedimethanamine 1477-55-0	Not Established	0.1 mg/m3 Ceiling	NIOSH: 0.1 mg/m3 Ceiling

SDS for: 399-Activator LT35 Black Page 3 of 6

1333-86-4	fraction)	TWA; 0.1 mg/m3 TWA (Carbon black in presence of Polycyclic aromatic hydrocarbons, as PAH)
-----------	-----------	---

Engineering Controls: Use appropriate engineering control such as process enclosures, local exhaust ventilation or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective, wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.

Eye / Face Protection: Wear protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulations.

Skin Protection: Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eye, skin or clothing.

Respiratory Protection: A NIOSH-approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air-purifying respirators is limited. Use a positive-pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where air-purifying respirators may not provide adequate protection.

General Hygiene Considerations: Avoid breathing vapor or mist. Avoid contact with eyes and skin. wash thoroughly after handling and before eating or drinking.

# **SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

#### Information on basic physical and chemical properties

Appearance: Liquid

Vapor Pressure: 0.27 mmHg

Vapor Density: Heavier than Air

Lbs / Gallon 9.28

Freezing point: No Data

Boiling range: 182°C

Evaporation rate: Slower than Ether

**Explosive Limits: 2%** 

Autoignition temperature: 715°C

Viscosity: No Data

Odor: Amine

Odor threshold: No Data

pH: No Data

Melting point: No Data

Solubility: Negligible

Flash point: 174 F,79 C

Flammability: No Data

Partition coefficient (n- No Data

octanol/water):

Decomposition temperature: No Data

VOC g/I 6.355

# **SECTION 10 - STABILITY AND REACTIVITY**

Chemical Stability: Stable under normal storage or use.

Conditions to Avoid: No further relavant information available.

Incompatible Materials: Avoid contact with peroxides, oxidizing materials, acids and alkalis.

Hazardous Decomposition Products: Incomplete combustion may produce nitogen oxides, carbon oxides, ammonia, phenol.

Hazardous Polymerization: Some combinations of resins and curing agents can produce exothermic reactions which in large masses can cause runaway polymerization and charing of the reactants. Reacts with peroxides, acids, alkalis and oxidizing agents.

# **SECTION 11 - TOXICOLOGICAL INFORMATION**

**Mixture Toxicity** 

Oral Toxicity LD50: 925mg/kg

SDS for: 399-Activator LT35 Black Page 4 of 6 Dermal Toxicity LD50: 1,975mg/kg Inhalation Toxicity LC50: 2,885mg/L

**Component Toxicity** 

108-95-2 Phenol

Oral LD50: 340 mg/kg (Rat) Dermal LD50: 630 mg/kg (Rabbit)

1477-55-0 1,3-Benzenedimethanamine

Oral LD50: 660 mg/kg (Rat) Dermal LD50: 2 g/kg (Rabbit) Inhalation LC50: 700 ppm (Rat)

Description CAS Number % Weight Carcinogen Rating

Carbon black .1 to 1.0% 1333-86-4 Carbon black: NIOSH: potential

occupational carcinogen

IARC: Possible human carcinogen

OSHA: listed

## **SECTION 12 - ECOLOGICAL INFORMATION**

No additional information provided for this product. See Section 3 for chemical specific data.

# **Component Ecotoxicity**

Phenol 96 Hr LC50 Pimephales promelas: 11.9 - 50.5 mg/L [flow-through]; 96 Hr LC50

Pimephales promelas: 20.5 - 25.6 mg/L [static]; 96 Hr LC50 Pimephales

promelas: 32 mg/L; 96 Hr LC50 Oncorhynchus mykiss: 5.449 - 6.789 mg/L [flowthrough]; 96 Hr LC50 Oncorhynchus mykiss: 7.5 - 14 mg/L [static]; 96 Hr LC50

Oncorhynchus mykiss: 4.23 - 7.49 mg/L [semi-static]; 96 Hr LC50

Oncorhynchus mykiss: 5.0 - 12.0 mg/L; 96 Hr LC50 Lepomis macrochirus: 13.5 mg/L [static]: 96 Hr LC50 Lepomis macrochirus: 11.9 - 25.3 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 11.5 mg/L [semi-static]; 96 Hr LC50 Poecilia reticulata: 34.09 - 47.64 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 31 mg/L [semi-static]; 96 Hr LC50 Brachydanio rerio: 27.8 mg/L; 96 Hr LC50 Cyprinus carpio: 0.00175 mg/L [semi-static]; 96 Hr LC50 Oryzias latipes: 33.9 - 43.3 mg/L

[flow-through]; 96 Hr LC50 Oryzias latipes: 23.4 - 36.6 mg/L [static]

48 Hr EC50 Daphnia magna: 4.24 - 10.7 mg/L [Static]; 48 Hr EC50 Daphnia

magna: 10.2 - 15.5 mg/L

96 Hr EC50 Pseudokirchneriella subcapitata: 46.42 mg/L; 96 Hr EC50 Pseudokirchneriella subcapitata: 0.0188 - 0.1044 mg/L [static]; 72 Hr EC50

Desmodesmus subspicatus: 187 - 279 mg/L [static]

# **SECTION 13 - DISPOSAL CONSIDERATIONS**

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classification of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidlines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and / or state and local guidelines.

#### **SECTION 14 - TRANSPORT INFORMATION**

**Proper Shipping Name UN Number Packing Group Hazard Class** Agency DOT Paint 3066

# **SECTION 15 - REGULATORY INFORMATION**

Additional regulatory listings, where applicable.

SDS for: 399-Activator LT35 Black Page 5 of 6

#### **CERCLA RQ:**

Component	RQ (lbs)
Phenol	500

SARA 311/312 Hazard Classes: Acute, Chronic, Fire

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING! This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

1333-86-4 Carbon black 0.1 to 1.0 % Carcinogen

# **SARA 302 Components:**

108-95-2 Phenol 20 to 30 %

#### **SARA 313 TOXIC CHEMICALS:**

108-95-2 Phenol 20 to 30 %

**Toxic Substances Control Act (TSCA):** All chemicals except those listed below appear in the Toxic Substances Control Act Chemical Substance Inventory.

- None

# **SECTION 16 - OTHER INFORMATION**

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations and orders.

Reviewer Revision

Date Prepared: 6/17/2015

SDS for: 399-Activator LT35 Black Page 6 of 6