# **SAFETY DATA SHEET**

# **SECTION 1 - PRODUCT & COMPANY IDENTIFICATION**

Product Name: #5 Product Code: S-#5

Trade Name: Solvent Adams Paint Mfg Company 1416 N University Ave

Lubbock, Tx 79415

Telephone Number: 806-763-2944 Web Site: adamspaintmfg.com

Product Use: See Product Data Sheet

Not recommended for: See Product Data Sheet

**Emergency Contacts & Phone Numbers** 

Chemtrec: 800-424-9300

SDS Request Line: 806-763-2944

# **SECTION 2 - HAZARDS IDENTIFICATION**

# **GHS Ratings:**

Flammable liquid	2	Flash point < 23°C and initial boiling point > 35°C (95°F)
Inhalation Toxicity	Acute Tox. 4	Gases>2500+<=5000ppm, Vapors>10+<=20mg/l,
		Dusts&mists>1+<=5mg/l
Skin corrosive	2	Reversible adverse effects in dermal tissue, Draize score: >=
		2.3 < 4.0 or persistent inflammation
Eye corrosive	2A	Eye irritant: Subcategory 2A, Reversible in 21 days
Reproductive toxin	1A	Based on human evidence
Aspiration hazard	1	Aspiration Toxicity Category 1: Known (regarded)- human
		evidence - hydrocarbons with kinematic viscosity ? 20.5
		mm2/s at 40° C.

### **GHS Hazards**

H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H360	May damage fertility or the unborn child

# GHS Pro

H360	May damage fertility or the unborn child		
recautions			
P201	Obtain special instructions before use		
P202	Do not handle until all safety precautions have been read and understood		
P210	Keep away from heat, sparks, open flames, hot surfaces and other ignition sources - No smoking		
P233	Keep container tightly closed		
P240	Ground and bond container and receiving equipment		
P241	Use explosion-proof electrical, ventilating, lighting and equipment		
P242	Use only non-sparking tools		
P243	Take precautionary measures against static discharge		
P261	Avoid breathing dust, fumes, gas, mist, vapors or spray		
P264	Wash thoroughly after handling		
P271	Use only outdoors or in a well-ventilated area		
P280	Wear protective gloves, protective clothing, eye protection and face protection		
P281	Use personal protective equipment as required		
P312	Call a POISON CENTER or physician if you feel unwell		
P321	Specific treatment (see Section 4 of SDS on this label)		

SDS for: S-#5 Page 1 of 6 P331 Do NOT induce vomiting

P362 Take off contaminated clothing and wash before reuse

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or physician

P302+P352 IF ON SKIN: Wash with soap and water

P303+P361+P353 IF ON SKIN: Take off immediately all contaminated clothing. Rinse skin with water P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable

for breathing

P305+P351+P338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact

lenses if present and easy to do - continue rinsing

P308+P313 IF exposed or concerned: Get medical attention P332+P313 If skin irritation occurs: Get medical attention

P337+P313 Get medical attention

P370+P378 In case of fire: Use dry chemical, foam, carbon dioxide or water fog for extinction

P405 Store locked up

P403+P235 Store in a well ventilated place. Keep cool

P501 Dispose of contents and container in accordance with local and national

regulations

#### Signal Word: Danger



#### **SECTION 3 - COMPOSITION INFORMATION ON INGREDIENTS**

Chemical Name	CAS number	Weight Concentration %
Toluene	108-88-3	50.00% - 60.00%
Acetone	67-64-1	40.00% - 50.00%

### **SECTION 4 - FIRST AID MEASURES**

<u>Inhalation</u>: If inhaled, remove to fresh air. If not breathing, give artifitial respiration or give oxygen by trained personnel. Seek immediate medical attention.

**Eye Contact**: Immediately flush eyes with plenty of water for 10 to 15 minutes. Get medical attention, if irritation or symptoms of overexposure persists.

**Skin Contact**: Immediately wash skin with soap and water. Get medical attention if irritation developes or persist. **Ingestion**: If swallowed, DO NOT induce vomiting. Call physician or poison control center immediately. Never give anything by mouth to an unconscious person.

<u>Other First Aid</u>: Due to possible aspiration into lungs, DO NOT induce vomiting if ingested. Provide a glass of water to dilute the material in the stomach. If vomiting occurs naturally, have person lean forward to reduce risk of aspiration.

# **SECTION 5 - FIRE FIGHTING MEASURES**

Flash Point: -20 C (-4 F)

LEL: 1.00 UEL: 13.00

<u>Suitable Extinguishing Media</u>: Use dry chemical, foam, carbon dioxide, or water fog to extinguish fire. Water may not be effective to extinguish fire. Spattering of flammable liquid may result from spraying water.

<u>Specific Hazards arising from the Chemical</u>: Minimize breathing gases, vapors, fumes or decomposition products. at elevated temperatures, vapors can form an ignitable mixture with air. Vapors can flow along surfaces to distant ignition sources and flash back. Closed containers may explode when exposed to heat.

SDS for: S-#5 Page 2 of 6

<u>Protection of Firefighters</u>: Water may be unsuitable as an extinguishing media, but helpful in keeping adjacent containers cool. If a leak or spill has ignited, use water spray to disperse the vapors and to protect the men attempting to stop leak.

<u>Protective Equipment and Precautions for Firefighters</u>: Wear self-contained breathing apparatus and full protective gear.

#### **SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Personal Precautions: Use proper personal protective equipment as listed in Section 8.

Environmental Precautions: Avoid runoff into storm sewers, ditches and waterways.

<u>Methods for Containment</u>: Contain spilled liquid with sand or earth. DO NOT use combustible materials, such as sawdust.

<u>Methods for Clean-up</u>: Remove all sources of ignition. Provide ventilation. Absorb spill with inert material (dry sand or earth), collect spill with a non-sparking tool then place in a chemical waste container for disposal.

#### **SECTION 7 - HANDLING AND STORAGE**

<u>Handling</u>: Use with adequate ventilation. Avoid breathing vapor and contacts with eyes, skin and clothing. Material will accumulate static charges which may cause an electrical spark (ignition source), bond and ground containers when transferring material. Use spark-proof tools and explosion-proof equipment. Do not reuse containers without proper cleaning or reconditioning.

<u>Hygiene Practices</u>: Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling vapor or mist. <u>Storage</u>: Store in a cool dry, well ventilated area away from sources of heat, combustible materials and incompatible substances. Keep container tightly closed when not in use.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION					
Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits		
Toluene 108-88-3	200 ppm TWA	20 ppm TWA	NIOSH: 100 ppm TWA; 375 mg/m3 TWA 150 ppm STEL; 560 mg/m3 STEL		
Acetone 67-64-1	1000 ppm TWA; 2400 mg/m3 TWA	750 ppm STEL 500 ppm TWA	NIOSH: 250 ppm TWA; 590 mg/m3 TWA		

Engineering Controls: Use appropriate engineering control such as process enclosures, local exhaust ventilation or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective, wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.

**Eye / Face Protection:** Wear protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulations.

<u>Skin Protection</u>: Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eye, skin or clothing.

Respiratory Protection: A NIOSH-approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air-purifying respirators is limited. Use a positive-pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where air-purifying respirators may not provide adequate protection.

<u>General Hygiene Considerations</u>: Avoid breathing vapor or mist. Avoid contact with eyes and skin. wash thoroughly after handling and before eating or drinking.

#### **SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

SDS for: S-#5 Page 3 of 6

#### Information on basic physical and chemical properties

Appearance: Liquid

Vapor Pressure: 174.6 mmHg

Vapor Density: Heavier than air

Lbs / Gallon 6.93
Freezing point: No Data

Boiling range: 56°C

Evaporation rate: Slower than Ether

Explosive Limits: 1% - 13%

Autoignition temperature: 465°C

Viscosity: No Data

Odor: Aromatic, sweet

Odor threshold: No Data

pH: No Data

Melting point: No Data
Solubility: Moderate

Flash point: -4 F,-20 C

Flammability: Flammable Liquid

Class IB

Partition coefficient (n- No Data

octanol/water):

**Decomposition temperature:** No Data

VOC g/I 869.973

### **SECTION 10 - STABILITY AND REACTIVITY**

**Chemical Stability: Stable** 

<u>Conditions to Avoid</u>: Heat, flames, sparks and other ignition sources. **Incompatible Materials:** Avoid contact with strong oxidizing agents.

Hazardous Decomposition Products: Incomplete combustion may produce carbon monoxide and other toxic gases.

Hazardous Polymerization: Will not occur.

### **SECTION 11 - TOXICOLOGICAL INFORMATION**

### **Mixture Toxicity**

Oral Toxicity LD50: 4,964mg/kg Inhalation Toxicity LC50: 19mg/L

#### **Component Toxicity**

108-88-3 Toluene

Oral LD50: 2,600 mg/kg (Rat) Inhalation LC50: 13 mg/L (Rat)

# **Miscellaneous Toxicological Information:**

**Notice:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

CAS NumberDescription% WeightCarcinogen RatingNoneNo Data

#### **SECTION 12 - ECOLOGICAL INFORMATION**

No additional information provided for this product. See Section 3 for chemical specific data.

#### **Component Ecotoxicity**

SDS for: S-#5 Page 4 of 6

Toluene 96 Hr LC50 Pimephales promelas: 15.22 - 19.05 mg/L [flow-through] (1 day old);

96 Hr LC50 Pimephales promelas: 12.6 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 5.89 - 7.81 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 14.1 - 17.16 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 5.8 mg/L [semi-static]; 96 Hr LC50 Lepomis macrochirus: 11.0 - 15.0 mg/L [static]; 96 Hr LC50 Oryzias latipes: 54 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 28.2 mg/L [semi-static];

96 Hr LC50 Poecilia reticulata: 50.87 - 70.34 mg/L [static]

48 Hr EC50 Daphnia magna: 5.46 - 9.83 mg/L [Static]; 48 Hr EC50 Daphnia

magna: 11.5 mg/L

96 Hr EC50 Pseudokirchneriella subcapitata: >433 mg/L; 72 Hr EC50

Pseudokirchneriella subcapitata: 12.5 mg/L [static]

Acetone 96 Hr LC50 Oncorhynchus mykiss: 4.74 - 6.33 mL/L; 96 Hr LC50 Pimephales

promelas: 6210 - 8120 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: 8300

mg/L

48 Hr EC50 Daphnia magna: 10294 - 17704 mg/L [Static]; 48 Hr EC50 Daphnia

magna: 12600 - 12700 mg/L

#### **SECTION 13 - DISPOSAL CONSIDERATIONS**

<u>Waste Disposal</u>: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classification of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidlines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and / or state and local guidelines.

### **SECTION 14 - TRANSPORT INFORMATION**

AgencyProper Shipping NameUN NumberPacking GroupHazard ClassDOTPaint Related Material1263II3

### **SECTION 15 - REGULATORY INFORMATION**

Additional regulatory listings, where applicable.

#### **CERCLA RQ:**

Component	RQ (lbs)	
Toluene	1000	
Acetone	5000	

SARA 311/312 Hazard Classes: Acute, Fire

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING!

This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

108-88-3 Toluene 50 to 60 % Carcinogen, Carcinogen

#### **SARA 302 Components:**

- None

#### **SARA 313 TOXIC CHEMICALS:**

108-88-3 Toluene 50 to 60 %

**Toxic Substances Control Act (TSCA):** All chemicals except those listed below appear in the Toxic Substances Control Act Chemical Substance Inventory.

- None

### **SECTION 16 - OTHER INFORMATION**

SDS for: S-#5 Page 5 of 6

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations and orders.

Reviewer Revision

Date Prepared: 6/17/2015

SDS for: S-#5 Page 6 of 6